NSN 5320-00-866-4670



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-00-866-4670 Fastener Length: 0.773 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.258 inches and 0.260 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** 0.507 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.344 inches and 0.407 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem **Shear Strength:** 5900 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Mechanical lock steel aisi 660, steel qq-s-633 comp c1144 Material: Steel comp 8740 stem **Material Specification:** Qq-w-405 federal specification 1st material response body or qq-w-405 federal specification 2nd material response body or mil-s-6758 military specification 2nd material response body **Surface Treatment:** Cadmium stem **Surface Treatment Specification:** Qq-p-416, type 2, cl3 federal specification single treatment response mechanical lock Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.