## NSN 5320-00-866-4894

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-866-4894

| Fastener Length:   |
|--|
| 0.592 inches   |
| Head Style:  |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)   |
| Shank Diameter:  |
| Between 0.162 inches and 0.164 inches  |
| Shank Style:   |
| Self-plugging mechanically locked stem   |
| Head Major Diameter:   |
| 0.333 inches   |
| Expansion Device:  |
| Serrated stem-type w   |
| Grip Length:   |
| Between 0.281 inches and 0.345 inches  |
| Hardness Rating:   |
| 48.0 rockwell c stem and 53.0 rockwell c stem  |
| Shear Strength:  |
| 2340 single pounds per square inch   |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees   |
| Special Features:  |
| Mechanical lock steel aisi 660, steel qq-s-633 comp c1144  |
| Material:  |
| Steel comp 8740 stem   |
| Material Specification:  |
| Qq-w-405 federal specification 1st material response body or qq-w-405 federal specification 2nd material response body or mil-s-6758 |
| military specification 2nd material response body  |
| Surface Treatment:   |
| Cadmium stem   |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, cl3 federal specification single treatment response mechanical lock  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A040a0   |
| Mil-std (military Standard):   |
| Mil-s-6049 spec.   |