# NSN 5320-00-866-4982

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-866-4982

# Fastener Length:

0.466 inches

# Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.162 inches and 0.164 inches

## Shank Style:

Self-plugging mechanically locked stem

### Head Major Diameter:

0.333 inches

Expansion Device:

Serrated stem-type w

### Grip Length:

Between 0.156 inches and 0.220 inches

### Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

### Shear Strength:

2340 single pounds per square inch

### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

# Special Features:

Mechanical lock steel aisi 660, steel qq-s-633 comp c1144

# Material:

Steel comp 8740 stem

# Material Specification:

Qq-w-405 federal specification 1st material response body or qq-w-405 federal specification 2nd material response body or mil-s-6758

military specification 2nd material response body

# Surface Treatment:

Cadmium stem

# Surface Treatment Specification:

Qq-p-416, type 2, cl3 federal specification single treatment response mechanical lock

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A040a0

#### Mil-std (military Standard):

Mil-s-6049 spec.