## NSN 5320-00-866-4987

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-866-4987 **Fastener Length:** 0.900 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.310 inches and 0.312 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** 0.634 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.406 inches and 0.470 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem **Shear Strength:** 8500 single pounds per square inch **Countersink Angle:** 

Between 99.0 degrees and 101.0 degrees

**Special Features:** 

Mechanical lock steel aisi 660, steel qq-s-633 comp c1144

Material:

Steel comp 8740 stem

**Material Specification:** 

Qq-w-405 federal specification 1st material response body or qq-w-405 federal specification 2nd material response body or mil-s-6758 military specification 2nd material response body

**Surface Treatment:** 

Cadmium stem

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl3 federal specification single treatment response mechanical lock

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.