

View Online at <https://aerobasegroup.com/nsn/5320-00-869-1487>

Thread Class:

3b

Thread Direction:

Right-hand

Collar Outside Diameter:

Between 0.512 inches and 0.518 inches

Collarheight:

Between 0.652 inches and 0.672 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Collar Inside Diameter:

Between 0.314 inches and 0.325 inches

End Application:

W/s: helicopter, ch-53a/d/e; helicopter, lamps mark iii, sh-60b; helicopter, rh-53; helicopter, cobra/tow, ah series; aircraft, thunderbolt ii, a-10; helicopter, iroquois hh/uh-1; helicopter, seahawk h-60; aircraft, stratolifter c-135; helicopter, advance attack, ah-1w; helicopter, mh-53e

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Collar Style:

Threaded (break off) type

Material:

Steel comp 303se body

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530g0