

View Online at <https://aerobasegroup.com/nsn/5320-00-875-9557>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.5670 inches and 0.5870 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

0.0780 inches

**Shank Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.3765 inches and 0.3813 inches

**Grip Length:**

Between 0.2450 inches and 0.2550 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.1900 inches

**Countersink Angle:**

100.0 degrees

**Special Features:**

Collar and washer included

**Material:**

Steel comp 4130 bolt or steel comp 4140 bolt or steel comp 8740 bolt

**Material Specification:**

Mil-s-6758 military specification 1st material response bolt or mil-s-5626 military specification 2nd material response bolt or mil-s-6049 military specification 3rd material response bolt

**Surface Treatment:**

Cadmium bolt

**Surface Treatment Specification:**

Qq-p-416, ty i, cl 3 federal specification single treatment response bolt

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6758 spec.