

View Online at <https://aerobasegroup.com/nsn/5320-00-875-9557>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.5670 inches and 0.5870 inches

Head Style:

Flush countersunk

Width Between Flats:

0.0780 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.3765 inches and 0.3813 inches

Grip Length:

Between 0.2450 inches and 0.2550 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.1900 inches

Countersink Angle:

100.0 degrees

Special Features:

Collar and washer included

Material:

Steel comp 4130 bolt or steel comp 4140 bolt or steel comp 8740 bolt

Material Specification:

Mil-s-6758 military specification 1st material response bolt or mil-s-5626 military specification 2nd material response bolt or mil-s-6049 military specification 3rd material response bolt

Surface Treatment:

Cadmium bolt

Surface Treatment Specification:

Qq-p-416, ty i, cl 3 federal specification single treatment response bolt

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.