NSN 5320-00-883-9387

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-883-9387

| Fastener Length: |
|--|
| 1.210 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.258 inches and 0.260 inches |
| Shank Style: |
| Self-plugging mechanically locked stem |
| Head Major Diameter: |
| 0.507 inches |
| Expansion Device: |
| Serrated stem-type w |
| Grip Length: |
| Between 0.781 inches and 0.845 inches |
| Hardness Rating: |
| 48.0 rockwell c stem and 53.0 rockwell c stem |
| Shear Strength: |
| 5900 single pounds per square inch |
| Countersink Angle: |
| 100.0 degrees |
| Material: |
| Steel comp 8740 stem |
| Material Specification: |
| Qq-w-405 federal specification 1st material response body or qq-w-405 federal specification 2nd material response body or mil-s-6758 |
| military specification 2nd material response body |
| Surface Treatment: |
| Cadmium stem |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |
| Mil-s-6049 spec. |
| |