

View Online at <https://aerobasegroup.com/nsn/5320-00-883-9406>

Fastener Length:

1.540 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.372 inches and 0.374 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.762 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.969 inches and 1.032 inches

Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

Shear Strength:

12200 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Mechanical lock steel aisi 660, or steel, qq-s-633 comp c1144

Material:

Steel comp 8740 stem

Material Specification:

Mil-s-6049 military specification single material response stem or astm a547 assn standard single material response stem

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.