# NSN 5320-00-883-9406

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-883-9406

# Fastener Length:

1.540 inches

# Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.372 inches and 0.374 inches

# Shank Style:

Self-plugging mechanically locked stem

# Head Major Diameter:

0.762 inches

# **Expansion Device:**

Serrated stem-type w

# Grip Length:

Between 0.969 inches and 1.032 inches

#### Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

# Shear Strength:

12200 single pounds per square inch

# **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

# **Special Features:**

Mechanical lock steel aisi 660, or steel, qq-s-633 comp c1144

#### Material:

Steel comp 8740 stem

# Material Specification:

Mil-s-6049 military specification single material response stem or astm a547 assn standard single material response stem

#### Surface Treatment:

Cadmium stem

# Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A040a0

# Mil-std (military Standard):

Mil-s-6758 spec.