

View Online at <https://aerobasegroup.com/nsn/5320-00-885-4820>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.155 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

0.2105 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

0.327 inches

**Tip Diameter:**

0.1951 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

0.875 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

108000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Major diameter: 0.2105 in.

**Material:**

Steel comp 8740 or steel comp e4340 or steel comp 4340

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5000 military specification 3rd material response

**Surface Treatment:**

Nickel and cadmium

**Surface Treatment Specification:**

Ams 2416 assn standard all treatment responses

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1724 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.