

View Online at <https://aerobasegroup.com/nsn/5320-00-902-9372>

Fastener Length:

0.334 inches

Head Style:

Hexagon

Head Height:

Between 0.125 inches and 0.135 inches

Shank Diameter:

Between 0.264 inches and 0.265 inches

Shank Style:

Collar and sleeve, self-plugging type

Expansion Device:

Threaded mandrel

Lubrication:

Dry film

Grip Length:

Between 0.156 inches and 0.219 inches

Width Across Flats:

Between 0.367 inches and 0.375 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Shear Strength:

9000 double pounds per square inch

Material:

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve and passivate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.