NSN 5320-00-903-2838

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-903-2838

| Fastener Length: |
|--|
| 0.295 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.123 inches and 0.128 inches |
| Shank Style: |
| Pull through hollow shank |
| Head Major Diameter: |
| 0.225 inches |
| Expansion Device: |
| Knob stem-type k |
| Grip Length: |
| Between 0.126 inches and 0.187 inches |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Nickel alloy 400 |
| Material Specification: |
| Qq-n-281 federal specification single material response |
| Surface Treatment: |
| Anodize or chromate |
| Surface Treatment Specification: |
| Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |
| Mil-a-8625 spec. |
| |