

View Online at <https://aerobasegroup.com/nsn/5320-00-903-6767>

**Fastener Length:**

Between 0.177 inches and 0.197 inches

**Head Style:**

Universal

**Head Height:**

Between 0.054 inches and 0.064 inches

**Shank Diameter:**

Between 0.124 inches and 0.128 inches

**Head Major Diameter:**

Between 0.238 inches and 0.262 inches

**Expansion Device:**

Drive stem-type h

**Grip Length:**

Between 0.078 inches and 0.109 inches

**Material:**

Steel comp 301 stem or steel comp 302 stem or steel comp 303 stem or steel comp 303f stem or steel comp 303s stem or steel comp 303se stem or steel comp 304 stem or steel comp 304l stem or steel comp 305 stem or steel comp 308 stem or steel comp 309 stem or steel comp 309s stem or steel comp 310 stem or steel comp 310s stem or steel comp 314 stem or steel comp 316 stem or steel comp 316l stem or steel comp 317 stem or steel comp 321 stem or steel comp 323 stem or steel comp 324 stem or steel comp 347 stem or steel comp 348 stem or steel comp 385 stem

**Material Specification:**

Qq-a-430 federal specification all material responses sleeve

**Surface Treatment:**

Anodize sleeve or chromate sleeve

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response sleeve or mil-c-5541 military specification 2nd treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.