## NSN 5320-00-905-1683



Solid Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-00-905-1683 Fastener Length: Between 0.615 inches and 0.635 inches **Head Style:** Undersized oval countersunk **Head Height:** Between 0.003 inches and 0.005 inches **Shank Diameter:** Between 0.124 inches and 0.127 inches **Shank Style:** Straight **Head Major Diameter:** Between 0.188 inches and 0.196 inches **Head Minor Diameter:** Between 0.134 inches and 0.144 inches **Countersink Height:** 0.029 inches **Grip Length:** 0.437 inches **Shear Strength:** 26000 single pounds per square inch **Countersink Angle:** Between 99.5 degrees and 100.5 degrees Material: Aluminum alloy 2117 **Material Specification:** Qq-a-430 federal specification single material response **Surface Treatment:** Anodize or oxide film **Surface Treatment Specification:** Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

## **Specification Data:**

80205-nas1097 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.