

View Online at <https://aerobasegroup.com/nsn/5320-00-907-3539>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.657 inches and 0.677 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.045 inches and 0.055 inches

**Width Between Flats:**

Between 0.079 inches and 0.081 inches

**Shank Diameter:**

Between 0.189 inches and 0.190 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.295 inches and 0.315 inches

**Grip Length:**

0.317 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

95000 single pounds per square inch

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5626 military specification 3rd material response or mil-s-6049 military specification 4th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.