

View Online at <https://aerobasegroup.com/nsn/5320-00-907-3653>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.655 inches

Head Style:

Flush countersunk

Shank Diameter:

0.2001 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

0.317 inches

Tip Diameter:

0.1951 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.375 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

108000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp 8740 or steel comp e4340 or steel comp 4340

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5000 military specification 3rd material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas1724 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.