

View Online at <https://aerobasegroup.com/nsn/5320-00-912-4857>

**Fastener Length:**

Between 0.251 inches and 0.281 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.103 inches and 0.113 inches

**Shank Diameter:**

Between 0.202 inches and 0.203 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Wax

**Grip Length:**

Between 0.031 inches and 0.094 inches

**Width Across Flats:**

Between 0.305 inches and 0.312 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Shear Strength:**

5240 double pounds per square inch

**Heat Treatment:**

Annealed

**Material:**

Steel comp 4130 nut or steel comp 8740 nut or steel comp 4140 nut

**Material Specification:**

Mil-s-6758 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut or mil-s-5626 military specification 3rd material response nut

**Surface Treatment:**

Cadmium nut and chromate nut

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.