

View Online at <https://aerobasegroup.com/nsn/5320-00-912-4857>

Fastener Length:

Between 0.251 inches and 0.281 inches

Head Style:

Hexagon

Head Height:

Between 0.103 inches and 0.113 inches

Shank Diameter:

Between 0.202 inches and 0.203 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Serrated stem-type w

Lubrication:

Wax

Grip Length:

Between 0.031 inches and 0.094 inches

Width Across Flats:

Between 0.305 inches and 0.312 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Shear Strength:

5240 double pounds per square inch

Heat Treatment:

Annealed

Material:

Steel comp 4130 nut or steel comp 8740 nut or steel comp 4140 nut

Material Specification:

Mil-s-6758 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut or mil-s-5626 military specification 3rd material response nut

Surface Treatment:

Cadmium nut and chromate nut

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.