# NSN 5320-00-915-4983

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-00-915-4983



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.655 inches and 0.675 inches

# Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

# Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3765 inches and 0.3813 inches

# Grip Length:

Between 0.370 inches and 0.380 inches

# Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

1920 pounds per square inch

# **Thread Size:**

0.190 inches

# Shear Strength:

5380 double pounds per square inch

# **Countersink Angle:**

100.0 degrees

# Material:

Titanium alloy uns r56400

# **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

# **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A528u0