

View Online at <https://aerobasegroup.com/nsn/5320-00-915-5073>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.760 inches and 0.780 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.095 inches and 0.097 inches

Shank Diameter:

Between 0.249 inches and 0.250 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.390 inches and 0.395 inches

End Application:

W/s: aircraft, prowler ea-6b; aircraft, intruder a-6e; fms-aircraft, hawkeye e-2c; aircraft, c-2a (reprocured); aircraft, hawkeye e-2c; aircraft, tomcat f-14

Grip Length:

0.380 inches

Thread Size:

0.250 inches

Countersink Angle:

100.0 degrees

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type 2, cl 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-8837 spec.