## NSN 5320-00-915-5077

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-915-5077 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.947 inches and 0.967 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.415 inches and 0.440 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.567 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 210000 pounds per square inch Hardness Rating: 45.0 rockwell c and 48.0 rockwell c **Thread Size:** 0.250 inches Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-00-915-5077

Pin-rivet - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-8837 spec.