## NSN 5320-00-916-4939

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-916-4939 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.935 inches and 0.955 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.095 inches and 0.097 inches **Shank Diameter:** Between 0.249 inches and 0.250 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.395 inches **Grip Length:** 0.630 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5320-00-916-4939

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.