

View Online at <https://aerobasegroup.com/nsn/5320-00-916-4972>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.685 inches and 0.705 inches

Head Style:

Err-090

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.095 inches and 0.097 inches

Shank Diameter:

Between 0.249 inches and 0.250 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Grip Length:

0.380 inches

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

50.0 rockwell c and 55.0 rockwell c

Thread Size:

0.250 inches

Shear Strength:

15300 double pounds per square inch

Special Features:

Single shear strength 156000

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response

Surface Treatment:

Nickel or cadmium

Surface Treatment Specification:

Ams 2416 assn standard 1st treatment response or mil-c-8837, type 2 cl 2 military specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-8837 spec.