## NSN 5320-00-916-4989

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-916-4989

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.565 inches and 0.585 inches
Head Style: Err-090
Head Height:  Between 0.064 inches and 0.074 inches
Width Between Flats:
Between 0.0791 inches and 0.0806 inches
Shank Diameter:
Between 0.1885 inches and 0.1895 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.357 inches and 0.377 inches
Lubrication:
Cetyl alcohol
Grip Length:
0.255 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
210000 pounds per square inch
Hardness Rating:
45.0 rockwell c and 48.0 rockwell c
Thread Size:
0.190 inches
Shear Strength:
7060 double pounds per square inch
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Mil-c-8837, type 2, cl 3 military specification single treatment response
Thread Series Designator:

Unjf

## NSN 5320-00-916-4989

Pin-rivet - Page 2 of 2



N/a	
Unit Of	Measure:

Shelf Life:

Demilitarization:

No

**Fiig:** A528u0

7.02040

Mil-std (military Standard):

Mil-c-8837 spec.