NSN 5320-00-917-2707

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-917-2707

Fastener Length:

Between 0.428 inches and 0.448 inches

Head Style:

Undersized oval countersunk

Head Height:

Between 0.004 inches and 0.006 inches

Shank Diameter:

Between 0.186 inches and 0.189 inches

Shank Style:

Straight

Head Major Diameter:

Between 0.297 inches and 0.302 inches

Head Minor Diameter:

Between 0.198 inches and 0.208 inches

Countersink Height:

0.046 inches

Grip Length:

0.157 inches

Shear Strength:

33000 single pounds per square inch

Countersink Angle:

Between 99.5 degrees and 100.5 degrees

Material:

Aluminum alloy 2017

Material Specification:

Qq-a-430 federal specification single material response

Surface Treatment:

Anodize or oxide film

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

Specification Data:

80205-nas1097 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.