

View Online at <https://aerobasegroup.com/nsn/5320-00-917-2753>

**Fastener Length:**

Between 0.713 inches and 0.743 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.202 inches and 0.203 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.378 inches and 0.385 inches

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Wax or dry film or cetyl alcohol or grease film

**Grip Length:**

Between 0.595 inches and 0.656 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c nut and 43.0 rockwell c nut

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 304 sleeve or steel comp 303 sleeve or steel comp 303f sleeve

**Material Specification:**

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or astm a582 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

**Surface Treatment:**

Cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.