

View Online at <https://aerobasegroup.com/nsn/5320-00-917-7941>

Fastener Length:

Between 0.543 inches and 0.573 inches

Head Style:

Hexagon countersunk

Head Height:

Between 0.049 inches and 0.059 inches

Shank Diameter:

Between 0.197 inches and 0.199 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded stem

Grip Length:

Between 0.345 inches and 0.406 inches

Width Across Flats:

Between 0.332 inches and 0.346 inches

Hardness Rating:

39.0 rockwell c bolt and 43.0 rockwell c bolt

Shear Strength:

3100 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 304 sleeve or steel comp 303 sleeve or steel comp 303f sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or astm a582 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium bolt and chromate bolt

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response bolt

Specification Data:

80205-nas1674 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.