# NSN 5320-00-926-5902

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-926-5902

## Fastener Length:

Between 0.490 inches and 0.510 inches

## Head Style:

Undersized oval countersunk

# Head Height:

Between 0.003 inches and 0.005 inches

## Shank Diameter:

Between 0.155 inches and 0.158 inches

#### Shank Style:

Straight

Head Major Diameter:

Between 0.240 inches and 0.247 inches

## Head Minor Diameter:

Between 0.185 inches and 0.195 inches

## **Countersink Height:**

0.037 inches

# Grip Length:

0.266 inches

#### Shear Strength:

26000 single pounds per square inch

## **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

#### Material:

Aluminum alloy 2117

## **Material Specification:**

Qq-a-430 federal specification single material response

## Surface Treatment:

Anodize or oxide film

## Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

#### **Specification Data:**

80205-nas1097 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A040a0

# Mil-std (military Standard):

Mil-a-8625 spec.