

View Online at <https://aerobasegroup.com/nsn/5320-00-927-4376>

**Fastener Length:**

Between 0.540 inches and 0.570 inches

**Head Style:**

Hexagon countersunk

**Head Height:**

Between 0.044 inches and 0.054 inches

**Shank Diameter:**

Between 0.162 inches and 0.164 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Threaded stem

**Grip Length:**

Between 0.345 inches and 0.406 inches

**Width Across Flats:**

Between 0.277 inches and 0.288 inches

**Hardness Rating:**

39.0 rockwell c bolt and 43.0 rockwell c bolt

**Shear Strength:**

1920 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp 304 sleeve or steel comp 303 sleeve or steel comp 303f sleeve

**Material Specification:**

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or astm a582 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

**Surface Treatment:**

Cadmium sleeve and chromate sleeve and passivate sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl2 federal specification 1st treatment response sleeve and qq-p-35 federal specification 2nd treatment response sleeve

**Specification Data:**

80205-nas1674 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.