NSN 5320-00-928-9923

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-928-9923

| Fastener Length: |
|--|
| 0.513 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| 0.156 inches |
| Shank Style: |
| Self-plugging |
| Head Major Diameter: |
| 0.286 inches |
| Expansion Device: |
| Plain stem-type t |
| Grip Length: |
| Between 0.313 inches and 0.375 inches |
| Countersink Angle: |
| 100.0 degrees |
| Special Features: |
| Sleeve orange color no. 32246 federal standard 595 |
| Heat Treatment: |
| H-38 strain hardened locking ring |
| Material: |
| Aluminum alloy 5056 locking ring |
| Material Specification: |
| Qq-a-430 federal specification single material response locking ring |
| Surface Treatment: |
| Anodize stem or chromate stem |
| Surface Treatment Specification: |
| Mil-a-8625 military specification 1st treatment response stem or mil-c-5541 military specification 2nd treatment response stem |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |
| Mil-a-8625 spec. |