

View Online at <https://aerobasegroup.com/nsn/5320-00-929-4162>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.7710 inches and 0.7960 inches

Head Style:

Err-090

Head Height:

Between 0.0820 inches and 0.0940 inches

Shank Diameter:

0.4068 inches

Shank Style:

Pin-riquet, tapered, threaded

Head Major Diameter:

Between 0.5820 inches and 0.5960 inches

Tip Diameter:

0.4010 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.3650 inches and 0.3800 inches

Thread Qty Per Inch (tpi):

24

Thread Size:

0.3750 inches

Shear Strength:

108000 single pounds per square inch

Material:

Steel comp 8740 or steel comp e4340

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Q-p-416, type 2, cl 2 federal specification 13th treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.