NSN 5320-00-929-4180

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-929-4180



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.697 inches and 0.722 inches

Head Style:

Err-090

Head Height:

Between 0.058 inches and 0.070 inches

Shank Diameter:

0.2636 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.379 inches and 0.389 inches

Tip Diameter:

0.2577 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.365 inches and 0.380 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

180000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

108000 single pounds per square inch

Material:

Steel comp 8740 or steel comp e4340

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1728 professional/industrial association standard

Shelf Life:

N/a

NSN 5320-00-929-4180

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

