# NSN 5320-00-929-4186

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-929-4186



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.885 inches and 0.910 inches

## Head Style:

Err-090

## Head Height:

Between 0.058 inches and 0.070 inches

#### Shank Diameter:

0.2766 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.392 inches and 0.403 inches

#### **Tip Diameter:**

0.2668 inches

#### Lubrication:

Cetyl alcohol

## Grip Length:

Between 0.552 inches and 0.567 inches

## Min. Tensile Strength (psi):

180000 pounds per square inch

## Thread Size:

0.250 inches

## Shear Strength:

108000 single pounds per square inch

#### Material:

Steel comp 8740 or steel comp 4340

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-00-929-4186

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

