

View Online at <https://aerobasegroup.com/nsn/5320-00-929-4210>

Fastener Length:

Between 0.478 inches and 0.508 inches

Head Style:

Hexagon countersunk

Head Height:

Between 0.044 inches and 0.054 inches

Shank Diameter:

Between 0.162 inches and 0.164 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded stem

Grip Length:

Between 0.282 inches and 0.344 inches

Width Across Flats:

Between 0.277 inches and 0.288 inches

Hardness Rating:

39.0 rockwell c bolt and 43.0 rockwell c bolt

Shear Strength:

1920 double pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp 304 sleeve or steel comp 303 sleeve or steel comp 303f sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or astm a582 assn standard 2nd material response sleeve or ams 52641 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve and chromate sleeve and passivate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response bolt

Specification Data:

80205-nas1674 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.