NSN 5320-00-929-6464

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-929-6464

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.256 inches

Head Style:

Flush countersunk

Shank Diameter:

0.3547 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.472 inches and 0.552 inches

Tip Diameter:

0.340 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.875 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Countersink Angle:

100.0 degrees

Material:

Steel comp 8740 or steel comp 4340

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-00-929-6464

Pin-rivet - Page 2 of 2

Fiig: A528u0

Mil-std (military Standard):

Mil-s-6049 spec.

