NSN 5320-00-929-6466

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-929-6466 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.381 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.3547 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.472 inches and 0.552 inches Tip Diameter: 0.337 inches Lubrication: Cetyl alcohol **Grip Length:** 1.000 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Countersink Angle:** 100.0 degrees Material: Steel comp 8740 or steel comp 4340 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-00-929-6466

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.