## NSN 5320-00-929-6499

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-929-6499 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.058 inches and 1.083 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.080 inches Width Between Flats: 0.329 inches **Shank Diameter:** 0.341 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.460 inches and 0.502 inches **End Application:** W/s: aircraft, stratofortress b-52; aircraft, starlifter c-141 **Grip Length:** 0.687 inches Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.312 inches **Special Features:** 0.341 in. Second shank dia, and lubrication Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf

-

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5320-00-929-6499

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.