# NSN 5320-00-929-6506

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-929-6506



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 0.808 inches and 0.833 inches

## Head Style:

Err-090

## Head Height:

Between 0.068 inches and 0.080 inches

#### Shank Diameter:

0.3417 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.490 inches and 0.502 inches

#### **Tip Diameter:**

0.3345 inches

#### Lubrication:

Cetyl alcohol

## Grip Length:

Between 0.427 inches and 0.442 inches

## Min. Tensile Strength (psi):

180000 pounds per square inch

## Thread Size:

0.312 inches

#### Shear Strength:

108000 single pounds per square inch

#### Material:

Steel comp 8740 or steel comp 4340

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-00-929-6506

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

