## NSN 5320-00-929-6520

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-929-6520 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.770 inches and 0.795 inches **Head Style:** Err-090 **Head Height:** Between 0.044 inches and 0.056 inches **Shank Diameter:** 0.2010 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.302 inches and 0.312 inches Tip Diameter: 0.1925 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.490 inches and 0.505 inches Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel comp 8740 or steel comp 4340 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1728 professional/industrial association standard Shelf Life:

N/a **Unit Of Measure:** 

## NSN 5320-00-929-6520

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0