NSN 5320-00-929-6522

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-929-6522 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.895 inches and 0.920 inches **Head Style:** Err-090 **Head Height:** Between 0.044 inches and 0.056 inches **Shank Diameter:** 0.200 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.312 inches and 0.323 inches Tip Diameter: 0.211 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.615 inches and 0.630 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1728 professional/industrial association standard Shelf Life:

N/a

NSN 5320-00-929-6522

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0