

View Online at <https://aerobasegroup.com/nsn/5320-00-929-9087>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.770 inches and 0.795 inches

Head Style:

Flush countersunk

Shank Diameter:

0.203 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.280 inches

Grip Length:

0.500 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

108000 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

0.211 in. Second shank dia, and lubrication cetyl alcohol

Material:

Steel comp e4340 or steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.