NSN 5320-00-929-9128

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-929-9128 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.621 inches and 0.646 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.326 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.494 inches Tip Diameter: 0.324 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.240 inches and 0.255 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.313 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5320-00-929-9128

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.