

View Online at <https://aerobasegroup.com/nsn/5320-00-929-9128>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.621 inches and 0.646 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

0.326 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

0.494 inches

**Tip Diameter:**

0.324 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.240 inches and 0.255 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.313 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.