

View Online at <https://aerobasegroup.com/nsn/5320-00-929-9179>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.3220 inches and 1.3470 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.0580 inches and 0.0700 inches

**Shank Diameter:**

0.2896 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

Between 0.3920 inches and 0.4030 inches

**Tip Diameter:**

0.2707 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.2400 inches and 0.2550 inches

**Thread Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Thread Size:**

0.2500 inches

**Shear Strength:**

108000 single pounds per square inch

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

**Surface Treatment:**

Cadmium or chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.