NSN 5320-00-929-9184

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-929-9184

Thread Class: 3a Thread Direction: Right-hand Fastener Length: Between 1.771 inches and 1.776 inches Head Style: Countersunk w/reverse chamfer Head Height: 0.081 inches Shank Diameter: 0.4053 inches Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 0.546 inches and 0.598 inches Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size: 0.250 inches
Thread Direction: Right-hand Fastener Length: Between 1.771 inches and 1.776 inches Head Style: Countersunk w/reverse chamfer Head Height: 0.081 inches Shank Diameter: 0.4053 inches Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 0.546 inches and 0.598 inches Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Right-hand Fastener Length: Between 1.771 inches and 1.776 inches Head Style: Countersunk w/reverse chamfer Head Height: 0.081 inches Shank Diameter: 0.4053 inches Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 0.546 inches and 0.598 inches Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Fastener Length: Between 1.771 inches and 1.776 inches Head Style: Countersunk w/reverse chamfer Head Height: 0.081 inches Shank Diameter: 0.4053 inches Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 0.546 inches and 0.598 inches Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Between 1.771 inches and 1.776 inches Head Style: Countersunk w/reverse chamfer Head Height: 0.081 inches Shank Diameter: 0.4053 inches Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 0.546 inches and 0.598 inches Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Head Style: Countersunk w/reverse chamfer Head Height: 0.081 inches Shank Diameter: 0.4053 inches Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 0.546 inches and 0.598 inches Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Countersunk w/reverse chamfer Head Height: 0.081 inches Shank Diameter: 0.4053 inches Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 0.546 inches and 0.598 inches Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Head Height: 0.081 inches Shank Diameter: 0.4053 inches Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 0.546 inches and 0.598 inches Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
O.081 inches Shank Diameter: O.4053 inches Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 0.546 inches and 0.598 inches Tip Diameter: O.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Shank Diameter: 0.4053 inches Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 0.546 inches and 0.598 inches Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
0.4053 inches Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 0.546 inches and 0.598 inches Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 0.546 inches and 0.598 inches Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Pin-rivet, tapered, threaded Head Major Diameter: Between 0.546 inches and 0.598 inches Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Head Major Diameter: Between 0.546 inches and 0.598 inches Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Between 0.546 inches and 0.598 inches Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Tip Diameter: 0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
0.3802 inches Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Lubrication: Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Cetyl alcohol Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Grip Length: Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Between 1.365 inches and 1.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
24 Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size:
180000 pounds per square inch Thread Size:
Thread Size:
0.250 inches
0.250 inches
Shear Strength:
108000 single pounds per square inch
Countersink Angle:
100.0 degrees
Material:
Steel
Material Specification:
Aisi e3310 assn standard single material response
, no. oco io acon otaniana on gio matoriai respense
Surface Treatment:
-
Surface Treatment:
Surface Treatment: Cadmium or cadmium and chromate or cadmium and phosphate

Unjf

NSN 5320-00-929-9184

Pin-rivet - Page 2 of 2



Specification Data	a
--------------------	---

80205-nas1724 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0