# NSN 5320-00-929-9185

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-929-9185



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.881 inches and 1.916 inches

## Head Style:

Countersunk w/reverse chamfer

### **Head Height:**

0.081 inches

## Shank Diameter:

Between 0.367 inches and 0.370 inches

### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

0.598 inches

# Grip Length:

Between 1.428 inches and 1.453 inches

# Thready Qty Per Inch (tpi):

24

# Thread Size:

0.375 inches

# Shear Strength:

108 single pounds per square inch

### **Countersink Angle:**

100.0 degrees

## **Special Features:**

0.472 in. Second shank dia

## Material:

Steel

## **Material Specification:**

Aisi e3310 assn standard single material response

### Surface Treatment:

Cadmium or cadmium and chromate or cadmium and phosphate

## Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

# **Thread Series Designator:**

Unjf

Shelf Life:

N/a

### Unit Of Measure:

---

# NSN 5320-00-929-9185

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

