## NSN 5320-00-929-9188

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-929-9188 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.010 inches and 1.035 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.2754 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.426 inches **Grip Length:** Between 0.677 inches and 0.692 inches **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Special Features:** 0.2642 in. Second shank dia, and lubrication cetyl alcohol Material: Steel comp 8740 or steel comp 4340 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1724 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No Fiig:

A528u0

## NSN 5320-00-929-9188

Pin-rivet - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.