## NSN 5320-00-929-9192

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-929-9192 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.645 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.2884 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.439 inches Tip Diameter: 0.2642 inches Lubrication: Cetyl alcohol **Grip Length:** 1.312 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** 0.288 in. Dia Material: Steel comp 8740 or steel comp e4340 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-00-929-9192

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.