## NSN 5320-00-929-9193

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-929-9193

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.771 inches and 1.776 inches

#### Head Style:

Flush countersunk

#### Shank Diameter:

Between 0.367 inches and 0.373 inches

### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.546 inches and 0.598 inches

#### Grip Length:

Between 1.365 inches and 1.380 inches

#### Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.375 inches

#### Shear Strength:

108 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### Material:

Steel

#### Material Specification:

Aisi e3310 assn standard single material response

## Surface Treatment:

Cadmium or cadmium and chromate or cadmium and phosphate

## Surface Treatment Specification:

Qq-p-416 federal specification all treatment responses

## **Thread Series Designator:**

Unjf

## Specification Data:

80205-nas1724 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No



# NSN 5320-00-929-9193

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

